



SPECIFICATIONS

| | |
|--------------------|-------------------|
| Frequency Range: | 6.0 - 26.5 GHz |
| Coupling: | 20.0 \pm 1.0 dB |
| Insertion Loss: | 0.90 dB Max |
| Coupling Flatness: | \pm 0.80 dB Max |
| Directivity: | 12 dB Min |
| VSWR: | 1.60:1 Max |
| Input Power: | 20 Watts Max |

Notes: Does not include coupling loss.
For load VSWR better than 1.20:1.

PULSAR MICROWAVE CORPORATION

PULSAR MICROWAVE CORPORATION
48 INDUSTRIAL WEST, CLIFTON NJ 07012
TEL: 973-779-6262 FAX: 973-779-2727
WWW.PULSARMICROWAVE.COM

DESCRIPTION :

Dual Directional Coupler

MODEL NO. :

CCS20-50-437/1

DIMENSIONS ARE IN INCHES
DECIMAL TOLERANCE:
2 PLACE \pm .02
3 PLACE \pm .010

SIZE
A

CAGE CODE :
0HR85

REV CODE :
180212

SCALE : N / A

ALL SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE AT ANY TIME

SHEET 1 OF 1