


# IDO-01-302

## QUADRATURE I.F. MIXER (DEMODULATOR)



### SPECIFICATIONS

Name:	IDO-01-302
Carrier (LO) Frequency:	10-20 MHz
RF Frequency:	LO $\pm$ 5 MHz
IQ Frequency:	DC-5 MHz
Conversion Loss:	10 dB max.
Amplitude Balance:	0.5 dB max.
Phase Balance:	5° max.
Isolation:	
L/R:	35 dB min.
L/I:	30 dB min.
VSWR:	1.5:1 min.
Connector Type:	Pin

### PORT CONFIGURATION

RF:	14
LO:	1
I:	12
Q:	5
Ground:	2-4, 6-11, 13

Specifications apply when operating LO power level is  $+10 \pm 0.5$  dBm and operating RF power level is  $-10 \pm 0.5$  dBm.  
IF Frequency (Q) is  $+90^\circ$  relative to IF frequency (I) when RF frequency is  $>$  LO frequency.

This is a commercial off the shelf (COTS) product.  
For an equivalent product that meets DFARS materials compliance, contact sales.  
All specifications are subject to change without notice at any time. Rev: 190403

www.pulsarmicrowave.com · 48 Industrial St West, Clifton NJ 07012 · Tel: 973-779-6262 · Fax: 973-779-2727 · sales@pulsarmicrowave.com

**PULSAR**  
MICROWAVE CORPORATION