IDO-04-F

QUADRATURE I.F. MIXER (DEMODULATOR)



SPECIFICATIONS

Name:	IDO-04-F
Carrier (LO) Frequency:	60-120 MHz
RF Frequency:	LO ± 20 MHz
IQ Frequency:	DC-20 MHz
Conversion Loss:	11 dB max.
Amplitude Balance:	0.6 dB max.
Phase Balance:	5° max.
Isolation:	
L/R:	35 dB min.
L/I:	30 dB min.
VSWR:	1.5:1 min.
Connector Type:	Surface

PORT CONFIGURATION

RF:	6
LO:	12
I:	9
Q:	3
Ground:	All Others

Specifications apply when operating LO power level is +10 ± 0.5 dBm and operating RF power level is -10 ± 0.5 dBm.
IF Frequency (Q) is +90° relative to IF frequency (I) when RF frequency is > LO frequency.

This is a commercial off the shelf (COTS) product.
For an equivalent product that meets DFARS materials compliance, contact sales.
All specifications are subject to change without notice at any time. Rev: 250614

www.pulsarmicrowave.com · 48 Industrial St West, Clifton NJ 07012 · Tel: 973-779-6262 · Fax: 973-779-2727 · sales@pulsarmicrowave.com